





Intelligent wireless communication

GSM RACK MOUNT SOLUTION GV-GSM-RM

The GV-GSM-RM is designed for advanced wireless monitoring, control and remote access.

With the GV-GSM-RM remote installations can be monitored and be wireless controlled by personnel over the GSM network. The unit can be configured to send text messages to a selected group of people when an input is activated or when a threshold value for an analogue input has been reached. Output signals can also be activated by the System Operator by sending text messages to the unit.

FEATURES

- · Advanced wireless monitoring
- · Controlled over the GSM network
- · All inputs and outputs can be activated by sending a individual text message
- Quad Band (850/900/1800/1900 Mhz)
- C € EU EMC Directive 2004/108/EU

Laegaardsvej 12 · 8520 Lystrup · Denmark Phone + 45 7022 8844 Fax + 45 7022 8866 www.hss.dk · info@hss.dk







HSS ADVANCED WARNING SYSTEMS



TECHNICAL DATA

110/220 VAC
850 / 900 / 1800 / 1900 MHz
Class 4 (2 W @ 800 / 900 MHz)
Class 1 (1 W @ 1800 /1900 MHz)
Class B, Multislot 10
-25° C - +65° C
5 - 90%
8.2 kg
Height: 2U Width: 19" (48,26 cm) Depth: 16.63" (42,25 cm)

