



GIANT VOICE®

EMERGENCY SYSTEMS



*Integrating
your warning
system to the
paging
system*

REMOTE PAGING CONTROLLER

GV-RPC

The Giant Voice® Remote Paging Controller provides interface between any PA/Paging System and your warning system control centre that allows you to broadcast warning tones and messages on your PA/Paging System.

The GV-RPC matches the output signal from your Whelen and Giant Voice® system and makes installation straightforward Plug and Play. The Audio and PTT output from the GV-RPC can be adjusted to match almost any type of PA/Paging System.

HSS

Laegaardsvej 12 · 8520 Lystrup · Denmark
Phone + 45 7022 8844
Fax + 45 7022 8866
www.hss.dk · info@hss.dk

ENGINEERING®
WARNING SYSTEM SOLUTIONS



GIANT VOICE®

EMERGENCY SYSTEMS

ALERTS
PEOPLE TO
POSSIBLE
DANGER



ORDERING INFORMATION

Product Description

Glant Voice® Remote Paging Controller VHF

Order No.

GV-RPC VHF A/D*

Product Description

Glant Voice® Remote Paging Controller UHF

Order No.

GV-RPC UHF A/D *

Product Description

Glant Voice® Remote Paging Controller Landline

Order No.

GV-RPC LL

*A = Analogue, D = Digital
REV. C

FEATURES

- Available in 2 versions: VHF/UHF radio or Landline
- Plug and Play connection to your Whelen or Giant Voice® Siren Control Center
- 2 audio outputs providing up to 15 Volts RMS @ 600 Ohms for balanced signals
- Configurable PTT outputs
- 2 independently adjustable audio levels
- Internal configurable jumper settings to include/exclude SI-Test® or PA.
- 19" Rack 2U for versatile mounting options
- Dual voltage power supply (100-240 VAC)

TECHNICAL DATA

Power Supply	100 - 240 VAC
Max Power Consumption	70 Watts (Radio Option) 20 Watts (Landline Option)
Frequency Response	VHF 403 - 470 MHz UHF 136 - 174 MHz Operating Temperature 0-60° C
Dimensions	Height: 2U Width: 19" (48,26 cm) Depth: 16.63" (42,25 cm)
Weight	8.2 kg

Laegaardsvej 12 · 8520 Lystrup · Denmark
Phone + 45 7022 8844
Fax + 45 7022 8866
www.hss.dk · info@hss.dk

HSS

ENGINEERING®
WARNING SYSTEM SOLUTIONS