

GIANT VOICE®

EMERGENCY SYSTEMS



*PA ceiling
mount speaker
with EN 54-24
certification*



PA CEILING SPEAKER

GV-SP6T-CM

GV-SP12T-CM

GV-SP20T-CM

With an EN 54-24 certification, the GV-SPxxT-CM ceiling mount speaker has been approved for voice alarm systems with operation in 100 V systems that an audio transformer has been integrated. In case of fire, the closed metal housing (fire protection cover) will restrict the spread of fires.

This speaker is the ideal solution for Public Address Systems in office environments, corridors and reception areas. The flush mount design offers a discrete installation and the spring locks make installation in ceiling plates fast and easy.

HSS

Laegaardsvej 12 · 8520 Lystrup · Denmark
Phone + 45 7022 8844
Fax + 45 7022 8866
www.hss.dk · info@hss.dk

ENGINEERING®
WARNING SYSTEM SOLUTIONS



GIANT VOICE®

EMERGENCY SYSTEMS

DISASTERS
HAPPEN, BE
PREPARED



FEATURES

- 100 V line technique
- Full range speaker with optimized voice reproduction
- Robust metal basket and protective grille
- Fire protection cover
- Quick mounting facility
- 3 power taps via push terminals
- Plastic cover with low mounting depth

TECHNICAL DATA

	GV-SP6T-CM	GV-SP12T-CM	GV-SP20T-CM
Power capability, 100 V	6/3/1.5 WRMS	12/6/3 WRMS	20/10/5 WRMS
Frequency range	120 – 15.000 Hz		
SPL	93 dB (1 W/m)		
Max. rated SPL	101 dB	103 dB	105 dB
Dimensions			
Diameter	ø200 mm		
Depth	70 mm		
Weight	800 g	980 g	1100 g
Mounting Cut-Out			
Diameter	ø180 mm		
Depth	60 mm		
Ceiling thickness	5 – 22 mm		
Operating Temperature	0° C to +40 °C		
Standards	EN 54-24 & EN 60849		

ORDERING INFORMATION

Product Description

Giant Voice® 6 Watt Ceiling Speaker

Order No.

GV-SP6T-CM

Product Description

Giant Voice® 12 Watt Ceiling Speaker

Order No.

GV-SP12T-CM

Product Description

Giant Voice® 20 Watt Ceiling Speaker

Order No.

GV-SP20T-CM

REV. D

HSS

Laegaardsvej 12 · 8520 Lystrup · Denmark
Phone + 45 7022 8844
Fax + 45 7022 8866
www.hss.dk · info@hss.dk

ENGINEERING®
WARNING SYSTEM SOLUTIONS